

Mobile Receipt & Label printer

PRN-M20



Ključne osobine

- Lako mijenjanje rolne
- Stand-by poslije 60s i gašenje poslije 60m
- Veliki broj interfejsa za povezivanje
- Integrirana podrška za QR CODE

PRIMJENA



Shopping



Mart



Restaurant



Hospital




Coffee Shop



Ticketing

Mobile receipt printer



Printing		PRN-M20
Printing method	Direct thermal	
Paper width	48mm	
Paper roll diameter	40mm	
Resolution	203 dpi	
Printing speed	90 mm/s	
Interface	USB / Serial / Bluetooth	
Line spacing	3.75mm (changeable using commands)	
Character size	ANK, Font A:1.5×3.0mm(12×24 dots) Font B:1.1×2.1mm(9×17 dots) Chinese, traditional Chinese:3.0×3.0mm(24×24 dots)	
Barcode Character		
Extended character sheet	PC347(Standard Europe) / Katakana/ PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French)/ PC865(Nordic) / West Europe/ Greek/ Hebrew/ East Europe/ Iran/ WPC1252/Pc866(Cyrillic#2) / PC852(Latin2)/ PC858/ IranII/ Latvian/ Arabic/ PT151(1251)	
Barcode types	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128	
2D Barcode	QR CODE	
Buffer		
Input buffer	4k bytes	
NV Flash	40k bytes	
Software		
Emulation	ESC/POS	
Driver	Windows/Linux/Android/Mac	
Utility	Windows & Linux test Utility	
SDK	iOS/Android/Windows	
Power		
Power adaptor	Input: AC 110V/240V, 50 ~ 60Hz Output: DC 9V/2A	
Battery	2000mAh/7.4V Lithium polymer battery	
Reliability		
Print head life	50 KM	
Physical characteristics		
Gross weight	0.225 kg	
Dimensions	114×80×50mm(D x W x H)	
Environmental Conditions		
Work environment	5 ~ 45°C, 10 ~ 80% RH	
Storage environment	-10 ~ 50°C, 10 ~ 90% RH (no condensation)	



Skenirajte QR kod za više informacija na našem websajtu.
Telefon: +382 20 231690
Web: www.raster.me
Email: info@raster.me

