



PRT101

Thermal Receipt Printer

- Poseban dizajn štiti od kapljica vode, masnoće i prašine
- Opcija i za WiFi i Bluetooth
- Integrisana podrška za QR CODE
- Može se okačiti na zid

PRIMJENE



Shopping



Mart



Hospital



Coffee Shop



Restaurant



Ticketing




Express



Factory

PRT101

Thermal Receipt Printer



Printing	
Printing method	Direct thermal
Paper width	79.5±0.5mm×φ80mm
Print width	72mm (adjustable by command)
Column capacity	576 dots/line(adjustable by command)
Printing speed	300 mm/s
Interface	USB+Serial+Lan (Bluetooth & WiFi optional)
Line spacing	3.75mm (Adjustable by commands)
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns
Character size	ANK, Font A: 1.5×3.0mm(12×24 dots) Font B: 1.1×2.1mm(9×17 dots)

Cutter	
Auto cutter	Partial

Barcode Character	
Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / Pc858 / IranII / Latvian / Arabic / PT151(1251)
Barcode types	UPC-A/UPC-E/JAN13(EAN13)/EAN8/CODE39/ITF/CODABAR/CODE93/CODE128
2D Barcode	QR CODE / PDF417
Input buffer	2048 Kbytes
NV Flash	256 Kbytes

Power	
Power adaptor	Input: AC 220V, 50 ~ 60Hz
Power source	Output: DC 24V/2.5A
Cash drawer output	DC 24V/1A

Physical characteristics	
Weight	1.78 Kg
Dimensions	198×148×138mm (D×W×H)

Environmental Requirements	
Work environment	Temperature (0 ~ 45°C) humidity(10 ~ 80%)
Storage environment	Temperature(-10 ~ 60°C) humidity(10 ~ 80%)

Reliability	
Cutter life	1.5 million cuts
Printer head life	150Km

Software	
Emulation	ESC/POS
Driver	Windows/JPOS/Linux/Android/Mac
Utility	Windows & Linux test Utility
SDK	iOS, Android, Windows



Skenirajte QR kod za više informacija na našem websajtu.
Telefon: +382 20 231690
Web: www.raster.me
Email: info@raster.me

